

Quality underlay for wood and laminate flooring

Sound-Guard is a high density foam underlay used to reduce footfall noise. With a heavy duty moisture-resistant PE face, it eliminates the need for a separate damp-proof membrane to be installed underneath. It is suitable for use with most floating engineered flooring, laminate flooring and bamboo flooring in both Residential and Commercial applications. Sound-Guard is also suitable for use with most types of underfloor heating

Features & Benefits

- Mid-range option for reducing footfall noise and sound transfer
- Suitable for use with most underfloor heating systems
- Heavy duty moisture-resistant PE face eliminates the need for a damp-proof membrane underneath
- Takes up minor imperfections in the subfloor
- Self-adhesive overlapping edges for easy installation

Compatibility	Suitable for use with most floating engineered flooring, laminate flooring and bamboo flooring. Suitable for use with most types of underfloor heating
Applications	Suitable for Residential and Commercial use
Composition	2mm IXPE closed-cell foam with heavy duty 0.15mm PE film face
Effectiveness	Up to 15% footfall noise reduction
Certification	N/A
Density	83kg/m ³
Colour	Green

Sizes available

Size	Type	Dimensions	Weight	Coverage	Code
10m ²	Roll	10m x 1m x 2mm	2.25kg	10m ²	SG10
25m ²	Roll	25m x 1m x 2mm	5.7kg	25m ²	SG25

Directions

Lay with PE film layer facing upwards.
Join, cut and fit as necessary until the required surface area is covered.