

Technical Datasheet

SOUND-GUARD XTREME UNDERLAY

High quality underlay for wood and laminate flooring

Sound-Guard Xtreme is a high performance natural rubber underlay with a nylon reinforced backing, designed for maximum sound reduction. It is suitable for use with most floating engineered flooring, laminate flooring, and bamboo flooring. It is suitable for use in residential and most commercial applications. Not recommended for use with underfloor heating

Features & Benefits

- Highly effective at reducing footfall noise and sound transfer
- Insulating foil layer
- Natural latex rubber
- Takes up minor imperfections in the subfloor
- Self-adhesive overlapping edges for easy installation

Compatibility	Suitable for use with most floating engineered flooring, laminate flooring and bamboo flooring. Not recommended for use with underfloor heating
Applications	Suitable for Residential and Commercial use
Composition	2.5mm Latex rubber with fleece surface and nylon reinforced backing
Effectiveness	Up to 15% footfall noise reduction
Certification	N/A
Density	750kg/m ³
Colour	Green with silver foil

Sizes available

Size	Type	Dimensions	Weight	Coverage	Code
10m ²	Roll	10m x 1m x 2.5mm	25kg	10m ²	SGX10

Directions

When installing over concrete, ensure that a polythene film moisture guard is installed first.

Lay with foil side up.

Join, cut and fit the Sound-Guard Xtreme as necessary until the required surface area is covered.

